76419 Hogwarts Castle and Grounds

 Installation requires a lot of patience and great observation that your LEGO bricks will come alive when you get this finished. The bricks with lighting as below, so make sure you're ready and let's get started.



Strategies for the Installation

This instruction divides three sections to complete the installation of the lighting set.

Section A: Check the type and quantity of components.

The quantity and type of components of each products are different and it needs to be carefully checked to make sure there do have enough material. The type of components is indicated by the label on the bag.

Section B: Test that each components is working properly.

Each components is made individually so it is necessary to test that each components is working properly to avoid the situation that the lighting does not work .

Section C: laying out components following the instruction.

Our material is very small but not fragile, just be reminded that don't to pull the wires too hard. For different people, there may be some installation steps that you can't understand. Please look at the previous and later installation step.

Section A: Check the type and quantity of components.

There are 17 bags in this set. The name and quantities of specific components are as shown , please check carefully.

Label	Content	Quantity
A01001 Light-15CM Warm White	Light-15CM Warm White	2
A01025 Light-15CM Cyan	Light-15CM Cyan	1
A01102 LED Strip Green	LED Strip Green	1
A01103 LED Strip Blue	LED Strip Blue	5
A01105 LED Strip Warm White	LED Strip Warm White	4
A012 Expansion Board	4 Socket Expansion Board	2
A01305 Power Supply	Power Supply	1
A01501 Connecting Cable 5CM	Connecting Cable 5CM	1
A01503 Connecting Cable 30CM	Connecting Cable 30CM	1
A01504 Connecting Cable 50CM	Connecting Cable 50CM	1
A01505 Connecting Cable 10CM	Connecting Cable 10CM	6
A01506 Connecting Cable 20CM	Connecting Cable 20CM	3
A02516 Light Strip-Warm White	Light Strip-Warm White	1
A02536 Light Strip-Warm White	Light Strip-Warm White	2
A03701 Remote Control	Remote Control	1
A1035 High-Brightness Light 15CM-Blue	High-Brightness Light 15CM-Blue	1
Components		

Please contact us immediately if there have any missing components.


Section B: Test that each components is working properly.

We need a structure to test all lights, so take out the bag with label "USB Power Cord" and "Expansion Boards" as follows.




It is worth reminding that our products are all customized. They have a unique way of connecting. The white plug on wire and the socket of the expansion board need to be connected together to transmit power.

Note that on one side of the white plug you can see two very small golden wires that should be connected to the two golden needles in socket of the expansion board.shown as blow.




All our connections between plug and socket are all the same as shown above. So for any such structure with plug and socket, please pay attention to the golden wire of the plug and the golden needle of the socket, they must be touched together.

The connection method between the USB Power Cord and Expansion Boards is as follows:



The USB Power Cord can be powered by phone chargers, power banks,etc.



This instruction will use the power bank as power supply . The test structure is shown as follow. All lamp in this set will be tested by this structure.



USB connectors to connect devices

When we test "A02516 Light Strip-Warm White" particles, Take out the bag labelled "A02516 Light Strip-Warm White". Take out one of the light and connect it to the socket. Turn on the power bank, the light will turn on normally as shown below.



Test each lamp according to this method. It should be noted that after the test, the lamp must be returned to the corresponding bag to avoid confusion of types.



LED strip test:

Take out the bag labeled "A01102 LED Strip Green". Take out the LED light bar, connect the USB power cable, turn on the mobile power supply, the light will be on normally, as shown in the figure below.



The components needs to be tested in this set is 2* Light-15CM Warm White,1* Light-15CM Cyan,5* LED Strip Blue,2* Light Strip-Warm White,4*LED Strip Warm White,1* High-Brightness Light 15CM-Blue.

Please contact us immediately if any components don't work.

Section C: laying out components following the instruction.

















<image>












































































































































































77



78

Remote control function description



ON: All branches are opened OFF: all branches are closed


- A: open/close A road
- B: open/close B road C: open/close C road
- D: open/close D road

FS: Turn on blinking for the last open channel BLN:Start breathing for the last


opened path


↑: Increase blinking/breathing rate
↓: Increase blinking/breathing rate


Brightness+: VIncrease brightness Brightness -: Reduce brightness The remote control does not contain batteries, please buy a CR2025 or CR2032 button battery in the nearest store and install it in the remote control.





79




















Good job, you've done all the installation steps, power it up and enjoy your work.



The battery box can also power the set. If it is necessary to change the power supply, prepare three AAA batteries, install them in the battery box, turn on the switch on the battery box, remove the plug of the USB Power Cable from the socket of the expansion board, plug the plug of the battery box to the same socket in the expansion board to power the suit as well.

THANKS